



## TECHNICAL DATA

Cycle times (*)	90 / 180 / 360 sec. and special cycles
Water consumption	2 l/rack
Tank capacity	10,6 l
Tank heating	1,7 kW
Power supply	400 / 50 / 3N (230 / 50 / 1)
Booster loading	
Standard	6,2 kW
Alternative	2,1 kW
Total loading	
Standard	6.8 kW   3 x 13 A
Alternative	2,7 kW   13 A
Wash pump	0.5 kW
Rack size	500 x 500   500 x 530 mm
Loading height	425 mm
Noise level	60,5 dB (A)
Weight (gross / net)	70 / 60 kg

## PRODUCT ADVANTAGES

- **VISIOTRONIC-TOUCH control:** single button control with colour code and remaining cycle time indication. With colour display and touch.
- **WASHSMART APP:** controlling your warewash operation with smart technology: status and messages, usage and operating cost, hygiene, order service and consumables
- **SENSO-ACTIVE resource management:** constantly measures the quality of the wash water and keeps the amount of rinsing needed in each rinse cycle to the minimum in order to guarantee a fully hygienic wash result
- **2IN1 double rack system:** two racks can be washed in a single wash cycle. One rack of cups can be washed underneath, while a second rack containing dishes and cutlery can also be washed above it. Thanks to the optimum use of the entire wash chamber the performance of the machine can be doubled
- **CLIP-IN wash and rinse arms:** wash and rinse arms can be removed with one hand and without any tools
- **Intelligent data documentation:** automatic recording of important operational data and consumptions and indication on the display
- **USB-interface:** comfortable download of operational data in form of a protocol via USB
- **GENIUS-X<sup>2</sup> fine filter system:** advanced filter system with pre-wash function reduces detergent consumption up to 35%
- **Interlocked strainer:** prevents operation without tank strainer
- **Optional refill signal:** monitors contents of external as well as integrated chemical containers
- **Hygiene programme:** for removal of calcium carbonate and other deposits from wash chamber

## CONNECTIONS

① Drain hose	2,000 mm   ID20/ OD25
② Supply hose	2,000 mm   R 3/4"
Required flow rate	5 l/min
Flow pressure	0.5 (0.8 with softener) - 10 bar
Max. supply water temperature	60 °C
③ Power cord	2,000 mm
Supply hose for	
④ Detergent	2,500 mm
⑤ Rinse aid	2,500 mm

\*Thermostop guarantees required temperatures with cold water and / or 230 V connection, the actual cycle times extend accordingly.

For machine protection the water hardness should not exceed 3°dH, if higher we recommend using an integrated water softener or an external water softener of the product line HYDROLINE PROTECT.

## DIMENSIONAL DRAWING

