



## TECHNICAL DATA

Cycle times (*)	52 / 70 / 170 / 180 sec. and special cycles
Water consumption	1.4 l/rack
Tank capacity	80 l
Tank heating	6.0 kW
Power supply	400 / 50 / 3N
Booster loading	
Standard	12.4 kW
Alternative	6.2 kW
Total loading	
Standard	23.5   3 x 40 A
Alternative	18.7   3 x 32 A
Wash pump	4 x 1.1 kW
Rack size	500 x 500 mm
Loading height	440 mm
Noise level	71 dB (A)
Weight (gross / net)	241 / 209 kg

## PRODUCT ADVANTAGES

- **PERMANENT-CLEAN automatic soil removal:** innovative filter system eliminates manual pre-cleaning. Soil is immediately removed into an external strainer, which saves operating costs and protects the machine
- **Double capacity:** the double wide wash chamber can cover 2 racks or bigger containers
- **VISIOTRONIC control:** single button control with remaining time indicator together with text and graphic display
- **SENSO-ACTIVE resource management:** constantly measures the quality of the wash water and keeps the amount of rinsing needed in each rinse cycle to the minimum in order to guarantee a fully hygienic wash result
- **ECO vapo rinse:** switchable steam rinse cycle reduces fresh-water consumption to 1.4 l/cycle. Saving of up to 44 % water and chemicals
- **Steam washing:** significantly less manual pre-cleaning and second runs by intensive wash cycles with steam
- **Exhaust energy storage:** the fully enclosed 4-sided hood keeps steam and energy inside the system: energy saving up to 6 kW; less humidity in the kitchen area and better hygienic conditions
- **CLIP-IN wash and rinse arms:** wash and rinse arms can be removed with one hand and without any tools
- **ROTOR-X wash system:** separate rotating upper & lower 4-spoke wash arms deliver dynamic wash power
- **POWER-PLUS wash programme:** selectable high-pressure programme to wash heavily soiled wash items
- **Filter position sensor:** prevents operation without tank strainer
- **Intelligent energy management:** the available energy is used continuously. Thus, at a low total loading value the heating time gets reduced
- **EASY-CLEAN concept:** blue markings in the machine help the operator to identify the components which require cleaning

\*Thermostop guarantees required temperatures with cold water, the actual cycle times extend accordingly.

For corner operation we recommend to make the right side of the machine accessible for service.

For machine protection the water hardness should not exceed 3°dH, if higher we recommend using an integrated water softener or a HOBART HYDROLINE water treatment system.

## CONNECTIONS

① Drain hose	2,000 mm   ID 20 / OD 25
② Supply hose	2,000 mm   R 3/4"
Flow pressure	0.5 bar
Max. supply water temperature	60 °C
Required flow rate	5 l/min
③ Power cord	2,500 mm
Supply hose for	
④ Detergent	2,000 mm
⑤ Rinse aid	2,000 mm
⑥ Drain hose PERMANENT-CLEAN	2,000 mm   ID 20 / OD 25

## DIMENSIONAL DRAWING

